



# MATERIAL SAFETY DATA SHEET

## 1. CHEMICAL PRODUCT AND COMPANY NAME

**Product name:** SUNSORB LS-119

**Use:** Stabilizer

**Manufacturer/Supplier:** Sin Hun Chemical Co., Ltd.  
No.2, 24th Rd., Taichung Industrial Park, Taichung City,  
Taiwan, R.O.C.

**Emergency Phone:** 886-4-2359-2565

**Fax:** 886-4-2359-2232

## 2. HAZARDS IDENTIFICATION

Xi: Irritant.

May cause sensitization by skin contact.

Do not breathe dust.

May cause an allergic skin reaction.

Avoid release to the environment.

## 3. COMPOSITION/ INFORMATION ON INGREDIENTS

**Chemical name:** 1,3,5-triazine-2,4,6-triamine,N,N''-[1,2-ethane-diyl-bis[[[4,6-bis-[butyl(1,2,2,6,6-pentamethyl-4-piperidinyl)amino]-1,3,5-triazine-2-yl]imino]-3,1-propanediyl]]-bis[N',N''-dibutyl-N',N''-bis(1,2,2,6,6-pentamethyl-4-piperidinyl)]

**CAS NO:** 106990-43-6

**Synonym:** Chimassorb 119

## 4. FIRST AID MEASURES

**Inhalation:** Material is not expected to be harmful if inhaled. Remove to fresh air.

**Skin contact:** Wash immediately with plenty of water and soap. Remove contaminated clothing and shoes without delay. Obtain medical attention. Do not reuse contaminated clothing without laundering. Destroy or thoroughly clean shoes before reuse.

**Eye contact:** Rinse immediately with plenty of water for at least 15 minutes.

**Ingestion:** If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

## 5. FIRE FIGHTING AND MEASURES

**Flammable limits:** Not applicable.

**Decomposition temp:** > 350°C

**Extinguishing media:** Water mist, carbon dioxide, foam, dry powder.

**Protective equipment for firefighters:** Use full protective clothing for chemicals and a self-contained breathing apparatus.



# MATERIAL SAFETY DATA SHEET

## 6. ACCIDENTAL RELEASE MEASURES

Wear appropriate personal protective equipment, including appropriate respirator protective to ventilate contaminated area. Contain spill if possible.

Wipe up or absorb on suitable material and shovel up. Prevent entry into sewers and waterways. Avoid contact with skin, eyes or clothing.

## 7. HANDLING AND STORAGE

**Handling precautions:** In accordance with good industrial practice, handle with care and avoid unnecessary personal contact. Avoid contact with eyes and prolonged or repeated skin contact. Avoid continuous or repetitive breathing of dust.

**Shipping and storing precautions:** Keep container tightly closed when not in use and during transport.

## 8. EXPOSURE CONTROLS AND PROTECTION

**Technical protective measures:** No special measure required.

**Exposure control limits:** None.

**Respiratory protection:** Wear suitable particular filter mask when exposed to dust.

**Hand protection:** Wear suitable gloves.

**Eye protection:** Wear suitable goggles or face protection.

**Skin protection:** Wear overall and closed fitwear.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** White to light yellow granules.

**Melting point:** 115~150°C

**Boiling point:** > 400°C

**Odour:** None.

**Flash point:** 278°C ASTM D92-78

**Solubility in water:** < 0.01%

**Ignition:** 330°C BAM

**Vapor pressure:** 4.7 E-11 Pa

## 10. STABILITY AND REACTIVITY

**Stability:** Stable.

**Conditions to avoid:** Static discharges.

**Materials to avoid:** Strong oxidizing agents, strong bases and strong acids.



# MATERIAL SAFETY DATA SHEET

## 11. TOXICOLOGICAL INFORMATION

**LD50 acute oral toxicity in rats:** > 2000mg/kg

**Skin irritation tested on rabbits:** Non-irritant.

**Eye irritation tested on rabbits:** Irritant.

**Skin sensitization on guinea pigs:** Negative.

## 12. ECOLOGICAL INFORMATION

Not available.

## 13. DISPOSAL CONSIDERATIONS

Incineration or landfill in accordance with local regulation.

Contaminated packaging material should be disposed of identically to the product itself.

Non contaminated packaging material should be treated as household waste or as recycling material.

## 14. TRANSPORT INFORMATION

**RID/ADR:** Free.

**IATA:** Free.

**IMDG-code:** Free.

**Flash point:** 278°C ASTM D92-78

## 15. REGULATORY INFORMATION

**EEC-symbol:** Xi = Irritant.

**Contains:** 1,3,5-triazine-2,4,6-triamine,N,N''-[1,2-ethane-diyl-bis[[[4,6-bis-[butyl (1,2,2,6,6-pentamethyl-4-piperidiny]amino]-1,3,5-triazine-2-yl]imino]-3,1-propanediyl]]-bis[N',N''-dibutyl-N',N''-bis(1,2,2,6,6-pentamethyl-4-piperidiny]]

**R 36:** Irritating to eyes.

**S 22:** Do not breathe dust.

**S 24/25:** Avoid contact with skin and eyes.

## 16. OTHER INFORMATION

**Shelf life:** 2 years minimum in sealed containers protect from light and air.

**Suggested uses:** A light stabilizer for UV systems.

The information and recommendations contained herein are based upon data believe to be correct. However, no guaranty or warranty of any kind expressed or implied is made with respect to the information contained here.

Material Safety Data Sheet